High-quality, fast 24"/A1 printing. Flexible functionality and low cost

iPF6400S

you can

8-colour large format printer designed for the Graphic Arts industries.
The iPF6400S produces high-quality, high-speed 24"/A1 prints for low cost.
Optional spectrophotometer also available.

24

2,400 X 1.200 DP

LUCIA EX 8 COLOURS

"HOT SWAP" INK TANKS

250GB HDD

PHOTOSHOP PLUG-IN

INBUILT COLOUR CALIBRATION

> A1 GLOSS 2.1 MINS

BORDERLESS PRINTING





iPF6400S WITH OPTIONAL SPECTROPHOTOMETER

Key features

- High-speed, economical printing
- LUCIA EX 8-colour ink gives you a broad colour gamut, with outstanding black reproduction
- Ideal for the production, photographic, design and exhibition industries
- High-capacity, 300ml ink tanks for greater productivity and reduced downtime
- 250GB HDD for efficient printing of complex jobs
- 'Hot Swap' ink tanks enable uninterrupted printing
- Manage print costs and track ROI with inbuilt accounting tool
- Inbuilt colour sensor ensures consistent and accurate colour reproduction
- Optional spectrophotometer for automated, high-precision colour management
- Added-value software provided as standard
- Optimal colour consistency between multiple 8 colour printers, using the "calibration link feature"







Specifications:imagePROGRAF iPF6400S

PRINTER MODEL	imagePROGRAF iPF6400S	
TECHNOLOGY		
Printer Type	8 Colour - 24"/609.6mm	
Print Technology	Canon Inkjet on Demand 6 colours integrated type (6 chips per print head x 2 print heads)	
Number of Nozzles	Total: 30,720 - MBK/BK/M/Y: 2,560 nozzles for each colour, C/PC/PM/GY: 5,120 nozzles for each colour	
Print Resolution	2,400 x 1,200dpi	
Nozzle Pitch	1200dpi x 2	
Line Accuracy	±0.1% or less	
Ink Droplet Size	4 Picoliter	
Ink Capacity	Bundled Starter Ink: 90ml - BK/MBK/M/Y 120ml - C/PC/PM/GY Sales Ink: 130ml or 300ml	
Ink Type	Pigment ink: LUCIA EX 8 colour pigment ink: BK, MBK, C, M, Y, PC, PM, GY	
OS Compatibility	Windows: XP/ Vista/7/8/Server 2003/2003 R2, Windows Server 2008 (32/64bit), Macintosh OSX 10.5.8-OS10.8.x	
Printer Languages	GARO (Graphic Arts language with Raster Operations)	
Standard Interfaces	USB 2.0 High-Speed Ethernet 10/100/1000 Base-T/TX	
Buffer RAM	256MB	
Hard Drive	250GB	
PRINTING SPEED (A1 Roll, Full Colour Image)		
Printing Speed (Plain Paper)	0.35 min (Fast Economy Mode) 1.56 min (Standard Mode)	
Printing Speed	1.02 min (Fast Economy Mode)	
(Coated Paper) Printing Speed	1.56 min (Standard Mode) 2.08 min (Fast Economy Mode)	
(Glossy Photo Paper)	3.08 min (Standard Mode)	
PAPER HANDLING		
Media Width	Roll paper and manual feed from top: 203.2mm (8inch) - 610mm (24inch) Manual feed from front: 250mm - 610mm (24inch)	
Media Thickness	Roll Unit: 0.07 - 0.8mm Top Loading Manual Feed 0.07 - 0.8mm Front Loading Manual Feed: 0.5 - 1.5mm	
Minimum Printable Length	Roll: 203.2mm (8inch) Manual feed from top: 279.4mm (11inch) Manual feed from front: 350mm	
Maximum Printable Length	18m (varies according to the OS and application) Manual feed from top: 1.6m Manual feed from front: 914mm	
Margins (Top, bottom, sides)	Recommended Area: Roll paper: Top: 20mm, Bottom: 5mm, Side: 5mm Manual feed from top: Top: 20mm, Bottom: 23mm, Side: 5mm Manual feed from front: Top: 20mm, Bottom: 23mm, Side: 5mm	
	Printable Area: ROll paper: Top: 3mm, Bottom: 3mm, Side: 3mm ROll paper borderless print: Top: 0mm, Bottom: 0mm, Side: 0mm Manual feed from top: Top: 3mm, Bottom: 3mm (*1), Side: 3mm **18ottom margin for art paper: 23mm Manual feed from front: Top: 3mm, Bottom: 23mm, Side: 3mm	
Maximum Media Roll Diameter	150.0mm	
	150.0mm Roll Feed: One Roll, top loading, front output Top Loading Manual Feed: One sheet, front output Front Loading Manual Feed: One sheet, front output	

DIMENSIONS AND WEIGHT Physical Dimensions - (W x D x H) Main unit with Auto Roll Feed Unit (standard): 1,227 (W) x 702 (D) x 344 (H) mm Weight: Approx. 54kg (excluding consumables a Main unit and Printer Stand: 1,227 (W) x 751 (D) x 1001 (H) mm Weight: Approx. 70kg (excluding consumables) Main unit with Printer Stand and Spectrophoton 1,227 (W) x 875 (D) x 1001 (H) mm Weight: Approx. 91kg (excluding consumables) SOFTWARE INCLUDED SOFTWARE INCLUDED Canon Printer Driver, Status Monitor, Free Layou Optimised Driver for AutoCAD, Media Configura (Windows only), Print Plug-in for Microsoft® Wor (Windows only), Print Plug-in for Adobe® Photo Photo Professional, Direct Print & Share (Windows REQUIREMENTS Power Supply AC 100 - 240 V (50 - 60 Hz)	nd Printer Stand)
(W x D x H) 1,227 (W) x 702 (D) x 344 (H) mm Weight: Approx. 54kg (excluding consumables a Main unit and Printer Stand: 1,227 (W) x 751 (D) x 1001 (H) mm Weight: Approx. 70kg (excluding consumables) Main unit with Printer Stand and Spectrophoton 1,227 (W) x 875 (D) x 1001 (H) mm Weight: Approx. 91kg (excluding consumables) SOFTWARE INCLUDED Canon Printer Driver, Status Monitor, Free Layou Optimised Driver for AutoCAD, Media Configura (Windows only), Print Plug-in for Microsoft® Wor (Windows only), Print Plug-in for Adobe® Photo Photo Professional, Direct Print & Share (Windows POWER AND OPERATING REQUIREMENTS Power Supply AC 100 - 240 V (50 - 60 Hz)	nd Printer Stand)
INCLUDED Optimised Driver for AutoCAD, Media Configura (Windows only), Print Plug-in for Microsoft® Wor (Windows only), Print Plug-in for Adobe® Photo Photo Professional, Direct Print & Share (Window OPERATING REQUIREMENTS Power Supply AC 100 - 240 V (50 - 60 Hz)	neter:
OPERATING REQUIREMENTS Power Supply AC 100 - 240 V (50 - 60 Hz)	tion Tool, PosterArtist Lite d/Excel/PowerPoint shop, Print Plug-in for Digital
117	
Power Consumption Operation: 100 W or less Power off (standby): 1W or less	
Operating	
Environment Temperature: 15 - 30°C, 10 - 80% (Condensation	free)
Noise Level (Approx.) Operation: 47 dB (A) or less Standby: 35 dB (A) or less Accoustic Power: 6.4 Bels Based on ISO 7779	
Regulations Europe: CE mark, Germany: TUV, Russia: Gost-R, Other Countries: CB Certification	
Environment Certificates ENERGY STAR (WW), RoHS directive, IT ECO Decl WEEE, ErP Lot 6 (Europe)	aration (Europe),
OPTIONS	
Printer Stand ST-28	
Roll Holder Set RH2-25	
Spectrophotometer unit SU-21	
CONSUMABLES	
Ink Tanks 130ml: PFI-106 BK/MBK/C/M/Y/PC/PM/GY 300ml: PFI-206 BK/MBK/C/M/Y/PC/PM/GY	
Print Head PF-05	
Maintenance Cartridge MC-16	

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and *: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

 $Can on \, recommends \, you \, use \, Can on \, Media \, for \, the \, best \, results. \, Please \, check \, media \, (paper) \, compatibility \, list \, to \, see \, which \, variety \, of \, paper/media \, is \, recommended.$

Genuine Canon ink cartridges are developed together with Canon large format printers as an important part of the large format printer printing system. Advanced technologies achieved by our research and development activities are incorporated into these ink cartridges. For optimum performance of Canon large format printers, Canon recommends use of genuine Canon ink cartridges.









Canon Inc.

Canon Europe canon-europe.com

09/13/v1 UK English edition © Canon Europa N.V., 2013



0800 018 23 23 sales@designsupply.com

